



IPC-4101D-WAM1

# Specification for Base Materials for Rigid and Multilayer Printed Boards

Developed by the Laminate/Prepreg Materials Subcommittee (3-11) of  
the Printed Board Base Materials Committee (3-10) of IPC

***Supersedes:***

IPC-4101D - April 2014  
IPC-4101C - August 2009  
IPC-4101B with  
Amendments 1 & 2 - April 2007  
IPC-4101B with  
Amendment 1 - February 2007  
IPC-4101B - June 2006  
IPC-4101A with  
Amendment 1 - June 2002  
IPC-4101A - December 2001  
IPC-4101 - December 1997  
IPC-L-108  
IPC-L-109  
IPC-L-112  
IPC-L-115  
IPC-AM-361

Users of this standard are encouraged to participate in the  
development of future revisions.

**Contact:**

IPC  
3000 Lakeside Drive, Suite 309S  
Bannockburn, Illinois  
60015-1249  
Tel 847 615.7100  
Fax 847 615.7105

# Table of Contents

<b>1 SCOPE</b> .....	1	3.4	Qualification Testing .....	7
1.1 Classification .....	1	3.4.1	Qualification Testing of Laminate .....	11
1.1.1 Specification Sheet Description .....	1	3.4.2	Qualification Testing of Prepreg .....	11
1.1.2 Nominal Laminate Thickness .....	1	3.5	Verification of Manufacturer's Quality System .....	11
1.1.3 Metal Cladding Type and Nominal Weight/Thickness .....	2	3.6	Conflict .....	11
1.1.3.1 Metal Cladding Type .....	2	3.7	Materials .....	11
1.1.3.2 Nominal Weight/Thickness .....	2	3.7.1	Metal Cladding .....	11
1.1.4 Thickness Tolerance (Laminate) .....	2	3.7.2	Reinforcement Fabric .....	11
1.1.5 Surface Quality Class .....	2	3.7.3	Resin Systems .....	11
1.1.6 Reinforcement Style .....	2	3.8	General Requirements .....	11
1.1.7 Prepreg Parameters .....	2	3.8.1	Fabricated Sheets and Panels .....	11
1.1.8 Color .....	4	3.8.1.1	Fabricated Laminate Sheet Material .....	11
1.1.8.1 Contrast Agents .....	4	3.8.1.2	Fabricated Laminate Panel Material .....	11
1.2 Dimensions and Tolerances .....	4	3.8.1.3	Fabricated Prepreg Panels .....	11
1.2.1 Metric and Imperial Measurements .....	4	3.8.1.4	Fabricated Prepreg Rolls .....	12
<b>2 APPLICABLE DOCUMENTS</b> .....	4	3.8.2	Inspection Lot .....	12
2.1 IPC .....	4	3.8.2.1	Inspection Lot for Laminate .....	12
2.2 National Conference of Standards Laboratories (NCSL) .....	6	3.8.2.2	Inspection Lot for Prepreg .....	12
2.3 International Standards .....	6	3.8.2.3	Preparation of Samples .....	12
2.4 Underwriters Laboratories (UL) .....	6	3.8.2.4	Etching Process and Etchant Removal for Copper Foil Specimens .....	12
2.5 European Union .....	6	3.8.2.5	Standard Laboratory Conditions .....	12
2.6 ASTM International .....	6	3.8.3	Visual Properties .....	12
<b>3 REQUIREMENTS</b> .....	6	3.8.3.1	Laminate Visual Properties .....	12
3.1 Terms and Definitions .....	6	3.8.3.1.1	Foil Indentations .....	12
3.1.1 Qualification Assessment .....	6	3.8.3.1.2	Wrinkles .....	12
3.1.2 Quality Conformance Testing .....	6	3.8.3.1.3	Scratches .....	13
3.1.3 Supplier's Quality System .....	6	3.8.3.1.4	Plastic Surface Finish of Metal-Clad Single-Sided Base Material .....	13
3.1.4 Process Control Testing .....	6	3.8.3.1.5	Surface Finish of Foil after Curing – Except Double Treat .....	13
3.1.5 Self Declaration .....	6	3.8.3.1.6	Surface and Subsurface Imperfections .....	13
3.1.6 Quality Assessment Data .....	7	3.8.3.2	Prepreg Visual Properties .....	13
3.1.7 Sample Qualification .....	7	3.8.3.2.1	Inclusions .....	13
3.1.8 Production Data .....	7	3.8.3.2.2	Impregnation Imperfections .....	13
3.1.9 Customer Test Data .....	7	3.8.4	Dimensional .....	14
3.1.10 Internal Assessment .....	7	3.8.4.1	Length and Width .....	14
3.1.11 Individual Customer Audit .....	7	3.8.4.1.1	Length and Width of Laminate .....	14
3.1.12 Independent Third Party Assessment .....	7	3.8.4.1.2	Length and Width of Prepreg .....	14
3.1.13 Epoxy, Multifunctional .....	7	3.8.4.1.3	Prepreg Roll Width .....	14
3.1.14 Epoxy, Difunctional .....	7	3.8.4.1.4	Prepreg Roll Length .....	14
3.1.15 AABUS .....	7	3.8.4.2	Thickness .....	14
3.2 Specification Sheets .....	7	3.8.4.2.1	Class A, B and C Laminate Materials .....	14
3.3 Manufacturer Quality Profile .....	7			

3.8.4.2.2	Class D Laminate Materials .....	14	3.10.1.1	Flammability .....	18
3.8.4.2.3	Class K, L and M Laminate Materials .....	15	3.10.1.2	Thermal Stress .....	18
3.8.4.2.4	Thickness Tolerance of Laminate Materials .....	15	3.10.1.3	Solderability .....	18
3.8.4.3	Bow and Twist of Laminate Materials .....	15	3.10.1.4	Chemical Resistance (Optional Test) .....	19
3.8.4.3.1	Sheets and Panels with Both Dimensions ≥300 mm [11.81 in] .....	15	3.10.1.5	Metal Surfaces Cleanability .....	19
3.8.4.3.2	Panels with One or Both Dimensions <300 mm [11.81 in] .....	15	3.10.1.6	Glass Transition Temperature (T <sub>g</sub> ) (Optional Test) .....	19
3.9	Physical Requirements .....	15	3.10.1.7	Delta T <sub>g</sub> (Optional Test) .....	19
3.9.1	Physical Requirements of Laminate Materials .....	15	3.10.1.8	Decomposition Temperature (Optional Test) .....	19
3.9.1.1	Peel Strength .....	15	3.10.1.9	Time to Delaminate (TMA) (Optional Test) .....	19
3.9.1.1.1	Peel Strength after Thermal Stress .....	16	3.10.2	Chemical Requirements of Prepreg Materials .....	20
3.9.1.1.2	Peel Strength at Elevated Temperature .....	16	3.10.2.1	Flammability .....	20
3.9.1.1.3	Peel Strength after Process Chemicals (Optional Test) .....	16	3.10.2.2	Chemical Resistance (Optional Test) .....	20
3.9.1.2	Dimensional Stability .....	16	3.10.2.3	Presence of Dicyandiamide (Dicy) (Optional Test) .....	20
3.9.1.3	Flexural Strength .....	16	3.11	Electrical Requirements .....	20
3.9.1.4	Flexural Strength at Elevated Temperature ...	17	3.11.1	Electrical Requirements of Laminate Materials .....	20
3.9.1.5	Thermal Conductivity [=] w/(m°K) .....	17	3.11.1.1	Permittivity .....	20
3.9.1.6	Coefficient of Thermal Expansion (CTE) (Optional Test) .....	17	3.11.1.2	Loss Tangent .....	20
3.9.1.7	Z-Axis CTE / Total Expansion (Optional Test) .....	17	3.11.1.3	Volume Resistivity .....	20
3.9.1.8	Fracture Toughness (Optional Test) .....	17	3.11.1.4	Surface Resistivity .....	20
3.9.2	Physical Requirements of Prepreg Materials .....	17	3.11.1.5	Arc Resistance .....	20
3.9.2.1	Resin Content .....	17	3.11.1.6	Dielectric Breakdown .....	20
3.9.2.1.1	Resin Content Percent (RC) (by Treated Weight) .....	17	3.11.1.7	Electric Strength .....	20
3.9.2.1.2	Resin Content Percent (RC) (by Burn-Off) .....	17	3.11.2	Electrical Requirements of Prepreg Materials .....	20
3.9.2.1.3	Treated Weight Total (TW) .....	17	3.11.2.1	Permittivity .....	20
3.9.2.1.4	Variation Within a Panel .....	17	3.11.2.2	Loss Tangent .....	20
3.9.2.2	Flow Parameter .....	17	3.11.2.3	Electric Strength .....	20
3.9.2.2.1	Resin Flow Percent (MF) .....	18	3.12	Environmental Requirements .....	20
3.9.2.2.2	Scaled Flow Thickness (SC) .....	18	3.12.1	Environmental Requirements of Laminate Materials .....	20
3.9.2.2.3	No Flow (NF) .....	18	3.12.1.1	Moisture Absorption .....	20
3.9.2.2.4	Rheological Flow (RE) .....	18	3.12.1.2	Fungus Resistance .....	21
3.9.2.2.5	Delta H (DH) .....	18	3.12.1.3	Pressure Vessel (Optional Test) .....	21
3.9.2.2.6	Percent Cure (PC) .....	18	3.12.1.4	Total Halogen Content (Optional Test) .....	21
3.9.2.2.7	Gel Time (GT) (Optional Test) .....	18	3.12.1.5	Conductive Anodic Filament (CAF) Growth (Optional Test) .....	21
3.9.2.2.8	Volatile Content (VC) (Optional Test) .....	18	3.12.2	Environmental Requirements of Prepreg Materials .....	21
3.9.2.2.9	Thermal Conductivity (Prepreg Reference) .....	18	3.12.2.1	Fungus Resistance .....	21
3.10	Chemical Requirements .....	18	3.12.2.2	Conductive Anodic Filament (CAF) Growth (Optional Test) .....	21
3.10.1	Chemical Requirements of Laminate Materials .....	18	3.13	Substitutability .....	21

3.13.1 Permissible Substitutions of Specification Sheet Materials ..... 21

3.13.2 Substitutability of Classes of Pits and Dents ..... 21

3.13.3 Substitutability of Classes of Thickness Tolerance ..... 21

3.13.4 Remarking of Substituted Laminates ..... 21

3.14 Marking ..... 21

3.14.1 Marking Laminate Materials ..... 21

3.14.2 Marking Prepreg Materials ..... 22

3.14.3 Marking of Shipping Containers ..... 22

3.15 Workmanship ..... 22

3.16 Material Safety ..... 22

3.17 Prepreg Shelf Life ..... 22

**4 QUALITY ASSURANCE PROVISIONS** ..... 22

4.1 Quality System ..... 22

4.2 Responsibility for Inspection ..... 22

4.2.1 Test Equipment and Inspection Facilities ..... 23

4.3 Qualification Testing ..... 23

4.3.1 Samples ..... 23

4.3.2 Frequency ..... 23

4.3.3 Laminator Qualification Profile ..... 23

4.3.4 Changes in Composition ..... 23

4.3.5 Qualification Data Retention ..... 23

4.4 Quality Conformance Inspection ..... 23

4.4.1 Frequency ..... 23

4.4.2 Acceptance Criteria ..... 24

4.4.3 Rejected Lots ..... 24

4.4.4 Conformance Data Retention ..... 24

4.4.5 Certificate of Conformance ..... 24

4.5 Statistical Process Control (SPC) ..... 24

**5 PREPARATION FOR DELIVERY** ..... 24

5.1 Packaging Materials ..... 24

5.2 Authorized Distributors ..... 24

**6 NOTES** ..... 25

6.1 Ordering Information ..... 25

6.1.1 Ordering Data for Laminate Materials ..... 25

6.1.2 Ordering Data for Prepreg Materials ..... 25

6.2 New Materials ..... 25

**7 KEYWORDS** ..... 26

7.1 Keyword Search Terms (Electronic/Soft Copy Searches) ..... 26

7.2 Segmented Keyword Search Terms and All Specification Sheets that Use the Specific Keywords for Searching ..... 26

7.3 Keyword Search Terms for All Specification Sheets ..... 26

**Figures**

Figure 3-1 Thickness Measurements for Laminates ..... 15

**Tables**

Table 1-1 Metal Cladding Types ..... 2

Table 1-2 Copper Foil Weight and Thickness ..... 3

Table 3-1 Reference Information and Test Frequency of Laminate ..... 8

Table 3-2 Reference Information and Test Frequency of Prepreg ..... 10

Table 3-3 Point Value for Longest Dimensions of Indentation ..... 12

Table 3-4 Surface Quality Classification ..... 13

Table 3-5 Permissible Variation in Length and Width of Laminates ..... 14

Table 3-6 Permissible Variation in Length and Width of Prepregs ..... 14

Table 3-7 Thickness and Tolerances for Laminates ..... 16

Table 3-8 Permissible Bow and Twist for Laminates, % .. 16

Table 3-9 Flammability Requirements ..... 19

Table 3-10 Permissible Laminate Substitutions for Specification Sheets /21, /24, /26 and /30 ..... 21

Table 4-1 Quality Conformance Plan for Monthly, Quarterly and Annual Tests – Laminate ..... 23

Table 4-2 Quality Conformance Plan for Monthly, Quarterly and Annual Tests – Prepreg ..... 23

# Specification for Base Materials for Rigid and Multilayer Printed Boards

## 1 SCOPE

This specification covers the requirements for base materials, herein referred to as laminate or prepreg, to be used primarily for rigid or multilayer printed boards for electrical and electronic circuits.

**1.1 Classification** The system shown below identifies clad and unclad laminate or prepreg base materials. The specification sheets serve as a cross-reference connecting the outlined callout system in this document to previously used systems.

Example for laminate base materials where this specification is referenced:

- L Material Designator (see 1.1.1)
- 25 Specification Sheet Number (see 1.1.1)
- 1500 Nominal Laminate Thickness (see 1.1.2)
- C1/C1 Metal Cladding Type and Nominal Weight/Thickness (see 1.1.3)
- A Thickness Tolerance Class (see 1.1.4)
- A Surface Quality Class (see 1.1.5)

Example for prepreg base materials where this specification is referenced:

- P Material Designator (see 1.1.1)
- 25 Specification Sheet Number (see 1.1.1)
- E7628 Reinforcement Style (see 1.1.6)
- TW Resin Content Method (see 1.1.7)
- RE Flow Parameter Method (see 1.1.7)
- VC Optional Prepreg Method (see 1.1.7)

**1.1.1 Specification Sheet Description** At the end of this document is a series of specification sheets. Each specification sheet outlines requirements for both laminate and prepreg for each product grade. The specification sheets are organized by a specific reinforcement type, resin system, and/or construction and are provided with a specification sheet number for ordering purposes. For convenience, the laminate and prepreg requirements for materials of the like composition are on the same specification sheet. Material Designator “L” indicates laminate material and Material Designator “P” indicates prepreg material as shown in designation examples in 1.1. When certifying to multiple specification sheets, the strongest performance requirements **shall** apply.

The headings for each specification sheet include reference definitions for the material, which cover the reinforcements, resin systems, flame retardants, and fillers used, as well as its other known identifications and glass transition temperature,  $T_g$ . The specific line items within the specification sheets are the requirements that material **shall** meet in order to be certified to this specification.

Specification sheets have no cancellation date. When no revision of IPC-4101 is called out, the latest revision of IPC-4101 **shall** apply. If previous revisions are used, then the specification sheet and revision **shall** be called out.

**1.1.2 Nominal Laminate Thickness** The nominal thickness is identified by four digits. For all substrates covered by this document, thicknesses may be specified or measured either over the cladding or over the dielectric (see 1.1.4 and 3.8.4.2). For metric specification, the first digit represents whole millimeters, the second represents tenths of millimeters, etc. For orders requiring Imperial units, the four digits indicate the thickness in ten-thousandths of an inch. In the example shown in 1.1, 1500 designates a laminate with thickness of 1.5 mm [0.0591 in], which would be specified as 0591 when using Imperial units.