



IPC-6902

# **Qualification and Performance Specification for Printed Electronics on Flexible Substrates**

Developed by the Printed Electronics Final Assembly Subcommittee  
(D-64) of the Printed Electronics Committee (D-60) of IPC

Users of this publication are encouraged to participate in the  
development of future revisions.

Contact:

IPC

# Table of Contents

<b>1</b>	<b>SCOPE</b>	1	3.3.5	Marking	8
1.1	Purpose	1	3.3.6	Defects in Printed Materials	9
1.2	Classification	1	3.3.7	Workmanship	9
1.3	Measurement Units	1	3.4	Dimensional Requirements	9
1.4	Definition of Requirements	1	3.4.1	Pattern Feature Accuracy	10
1.5	Process Control Requirements	1	3.4.2	Bow and Twist (Rigid Areas)	10
1.6	Order of Precedence	2	3.4.3	Flex (Nonrigid Areas)	10
1.6.1	Conflict	2	3.5	Printed Materials Mechanical Requirements	10
1.6.2	Clause References	2	3.6	Nonprinted Solderable Surfaces	10
1.6.3	Appendices	2	3.7	Structural Integrity	10
1.7	Use of “Lead”	2	3.7.1	Requirements for Coupons or Flexible Printed Electronic Devices after Thermal Stressing	10
1.8	Abbreviations and Acronyms	2	3.8	Electrical Requirements	11
1.9	Terms and Definitions	2	3.8.1	Dielectric Withstanding Voltage	11
1.9.1	Crease	2	3.8.2	Electrical Continuity and Isolation Resistance	12
1.9.2	Via	2	3.8.3	Moisture and Insulation Resistance (MIR)	12
1.9.3	Foreign Object Debris (FOD)	2	3.9	Special Requirements	13
1.10	Printed Electronics Types	2	3.9.1	Outgassing	13
1.11	Standard Printed Electronic Design	3	3.9.2	Fungus Resistance	13
1.12	Selection for Procurement	3	3.9.3	Vibration	13
1.12.1	Production Master and Database	3	3.9.4	Mechanical Shock	13
1.12.2	Deviations and Waivers	4	3.9.5	Impedance Testing	13
1.12.3	Selection (Default)	4	3.9.6	Coefficient of Thermal Expansion (CTE)	13
<b>2</b>	<b>APPLICABLE DOCUMENTS</b>	4	3.9.7	Thermal Shock	13
2.1	IPC	4	3.9.8	Surface Insulation Resistance (As Received)	13
2.2	ASTM International	5	3.9.9	Ultraviolet (UV) Resistance	13
2.3	JEDEC	5	3.9.10	Material Removal or Replacement	14
<b>3</b>	<b>REQUIREMENTS</b>	6	3.9.11	Simulation for Component Assembly and Rework	14
3.1	General	6	3.9.12	Flexibility Endurance	14
3.2	Materials	6	3.9.13	Adhesion	14
3.2.1	Flexible Base Materials	6	3.9.14	Destructive Physical Analysis (DPA)	14
3.2.2	External Bonding Materials	6	3.9.15	Solderability	14
3.2.3	Printed Dielectric Materials	6	3.9.16	Abrasion Resistance	14
3.2.4	Printed Conductive Materials	6	3.9.17	Accelerated Aging	14
3.2.5	Printed Passive Materials	6	3.9.18	Silver Migration	14
3.2.6	Marking Inks	6	3.9.19	Current Carrying Capacity	14
3.2.7	Final Finishes, Coatings and Platings (Metallic and Nonmetallic)	6	3.9.20	Repair	14
3.3	Visual Examination	6	3.9.21	Rework	14
3.3.1	Visual Imperfections	7	<b>4</b>	<b>QUALITY ASSURANCE PROVISIONS</b>	14
3.3.2	Registration	8	4.1	Responsibility for Inspection	14
3.3.3	Dielectric Wetting	8	4.1.1	Test Equipment and Inspection Facilities	14
3.3.4	Adhesion	8			

4.1.2	Contract Services .....	15
4.2	Materials Inspection .....	15
4.3	Quality Conformance Inspection .....	15
4.3.1	Inspection of Product for Delivery .....	15
4.3.2	Quality Conformance .....	15
4.4	Reliability Test and Evaluation .....	18
4.4.1	Noncompliance .....	18
4.5	Qualification .....	18
4.5.1	Sample Test Coupons .....	18
4.6	Acceptance Testing and Frequency .....	18
4.6.1	C=0 Zero Acceptance Number Sampling Plan .....	19
4.6.2	Additional Test Coupons for Suspected Isolated Defects .....	19
<b>5</b>	<b>NOTES</b> .....	19
5.1	Ordering Data .....	19
<b>APPENDIX A</b>	<b>Index of Acronyms and Abbreviations</b> .....	20

## Figures

Figure 1-1	Example of Printed Electronic Using Every Standard Printed Electronic Design (SPED) Type in One Device .....	3
Figure 3-1	Surface Mount Land Defects .....	7
Figure 3-2	Foreign Object Debris (FOD) .....	8
Figure 3-3	Conductor Overlap .....	8
Figure 3-4	Variation in Conductor Height and Width .....	9
Figure 3-5	Voids in Printed Dielectric Between Printed Conductors .....	9
Figure 3-6	Conductive Hole Fill Class 2 and 3 .....	11
Figure 3-7	Conductive Hole Fill Class 1 .....	11
Figure 3-8	Resistive Continuity Test Illustrations (Network Resistance) .....	12

## Tables

Table 1-1	Default Requirements .....	4
Table 3-1	Dielectric Withstanding Test Voltages .....	12
Table 3-2	Insulation Resistance .....	12
Table 3-3	Surface Insulation Resistance .....	13
Table 4-1	Qualification Testing and Acceptance Testing Frequency .....	15
Table 4-2	C=0 Sampling Plan Per Lot Size .....	19

---

# Qualification and Performance Specification for Printed Electronics on Flexible Substrates

---

## 1 SCOPE

This standard establishes and defines the qualification and performance requirements for printed electronics and their forms of component mounting and interconnecting structures on flexible substrates. Flexible substrates, as pertain to this standard, are materials or devices which have some amount of flexibility or bendability but are not considered to be stretchable (e.g., fabrics, textiles, stretchable polymers, etc.). The substrate can be conductive, semiconductive or nonconductive.

**1.1 Purpose** The purpose of this specification is to provide requirements for qualification and performance of flexible printed electronics designed to IPC-2292.

**1.2 Classification** IPC standards recognize that electrical and electronic assemblies are subject to classifications by intended end-item use. Three general end-product classes have been established to reflect differences in manufacturability, complexity, functional performance requirements, and verification (inspection/test) frequency. It should be recognized that there may be overlaps of equipment between classes.

### **CLASS 1 General Electronic Products**

Includes products suitable for applications where the major requirement is function of the completed assembly.

### **CLASS 2 Dedicated Service Electronic Products**

Includes products where continued performance and extended life is required, and for which uninterrupted service is desired but not critical. Typically, the end-use environment would not cause failures.

### **CLASS 3 High Performance/Harsh Environment Electronic Products**

Includes products where continued high performance or performance-on-demand is critical, equipment downtime cannot be tolerated, end-use environment may be uncommonly harsh, and the equipment must function when required, such as life support or other critical systems.

**1.3 Measurement Units** All dimensions and tolerances in this specification are expressed in hard SI (metric) units. Users of this specification are expected to use metric dimensions. All dimensions  $\geq 1$  mm will be expressed in millimeters. All dimensions  $< 1$  mm will be expressed in micrometers.

**1.4 Definition of Requirements** The words **shall** or **shall not** are used in the text of this document wherever there is a requirement for materials, preparation, process control or acceptance.

The word “should” reflects recommendations and is used to reflect general industry practices and procedures for guidance only.

Line drawings and illustrations are depicted herein to assist in the interpretation of the written requirements of this Standard. The text takes precedence over the figures.

**1.5 Process Control Requirements** The primary goal of process control is to continually reduce variation in the processes, products, or services to provide products or processes meeting or exceeding User requirements. Process control tools such as IPC-9191, JEDEC JESD 557 or other User-approved system may be used as guidelines for implementing process control.

Manufacturers of Class 3 products **shall** develop and implement a documented process control system.

A documented process control system, if established, **shall** define process control and corrective action limits.

This may or may not be a statistical process control system. The use of “statistical process control” (SPC) is optional and should be based on factors such as design stability, lot size, production quantities, and the needs of the Manufacturer.