



IPC-9797

Press-Fit Standard for Automotive Requirements and Other High-Reliability Applications

Developed by the Cold Joining Press-Fit Task Group (5-21m) of the
Assembly and Joining Committee (5-20) of IPC

Users of this publication are encouraged to participate in the
development of future revisions.

Contact:

IPC

Table of Contents

1 Scope	1	2.1 IPC Documents	6
1.1 Purpose	1	2.2 Joint Industry Documents	7
1.2 Classification	1	2.3 JEDEC	7
1.3 Measurement Units	1	2.4 International Electrotechnical Commission Documents	7
1.3.1 Verification of Dimensions	1	2.5 ASTM	7
1.4 Definition of Requirements	1	2.6 Automotive Industry Action Group Documents	7
1.4.1 Acceptance Criteria	2	2.7 International Organization for Standardization (ISO)	7
1.5 Process Control Requirements	3	3 REQUIREMENTS	7
1.6 Order of Precedence	3	3.1 Compliant Press-Fit Pin Requirements	7
1.6.1 Conflict	3	3.1.1 Cleanliness Requirements	7
1.6.2 Appendices	3	3.1.2 Design Requirements	7
1.7 Use of “Lead”	3	3.1.3 Compliant Press-Fit Pin Contact Finish Requirements	8
1.8 Abbreviations and Acronyms	3	3.2 Requirements for Printed Boards for Press-Fit Technology	8
1.9 Terms and Definitions	3	3.2.1 Printed Circuit Board Design Requirements	8
1.9.1 Compliant Press-Fit Pin Connection	3	3.2.2 Material Requirements	9
1.9.2 Compliant Press-Fit Pin	3	3.2.3 Surface Finish	9
1.9.3 Compliant Press-Fit Zone	3	3.2.4 Printed Board Requirements for Qualification and Test of Compliant Press-Fit Zones	9
1.9.4 Contact Area	4	4 TESTS	9
1.9.5 Deposition of Surface Finishes	4	4.1 General	9
1.9.6 Pad Lifting	4	4.2 Unassembled Tests – Test Group A	12
1.9.7 Pad Bulging	4	4.2.1 Examination of Pin and Test-Printed Board Dimensions – A1	12
1.9.8 Laminate Buckling	4	4.2.2 Optical Inspection of Surface Condition – A2	12
1.9.9 Whitening	4	4.2.3 Adhesion Test – A3	12
1.9.10 Intimate Metal to Metal Connection	4	4.2.4 Spring-Force Measurement – A4	13
1.9.11 Jet-Effect Deformation j	4	4.2.5 Cross Sections of Pins and Printed Board – A5 ..	13
1.9.12 Pin Shaft	4	4.3 Assembled Tests – Test Group B to F	14
1.9.13 Pin Neck	4	4.3.1 Push-In and Measurement of Push-In Force – B1, C1, D1, E1, F1	14
1.9.14 Pin Shoulder	4	4.3.2 Storage – B2, C2, D2, E2	14
1.9.15 Compliant Press-Fit Zone Tip	4	4.3.3 Optical Inspection on Protrusion and Insertion Side – B3, C3+C6, D3+D10, E3+E7	14
1.9.16 Strip and Strip Thickness	4	4.3.4 Contact Resistance – B4, C4+C7, D4+D11, E4+E8	14
1.9.17 Push-In Force	4	4.3.5 Push-Out and Measurement of Push-Out Force – B5, C8, D12, E9	15
1.9.18 Push-Out Force	5	4.3.6 Transverse and Longitudinal Cross-Sections – B6, C9, D13, E10	15
1.9.19 Pull-Out Force	5	4.4 Environmental Tests – Test Groups C, D, E	17
1.9.20 Push-Through Force	5	4.4.1 Temperature Cycle – C5, D5, E5	17
1.9.21 Electrical Clearance	5	4.4.2 Climatic Sequence – D6	17
1.9.22 User	5	4.4.3 High Temperature Storage – D7	17
1.9.23 Manufacturer (Assembler)	5	4.4.4 Flowing Mixed Gas Corrosion Test – D8	17
1.9.24 Supplier	6		
1.10 Additional Requirements	6		
1.10.1 Requirements Flowdown	6		
1.10.2 Personnel Proficiency	6		
1.11 Inspection Methodology	6		
1.11.1 Lighting	6		
1.11.2 Magnification Aids	6		
2 APPLICABLE DOCUMENTS	6		

4.4.5 Vibration Test – E6 18

4.5 Whisker Test 18

4.5.1 2000 H Storage – E2 18

5 Acceptance Criteria 19

5.1 Test Group A 19

5.1.1 Adhesion 19

5.2 Acceptance Criteria for Test Groups B-E 20

5.2.1 Optical Inspection 20

5.2.2 Cross-Sectional Criteria 28

5.3 Mechanical 36

5.3.1 Push-In Force 36

5.3.2 Push-Out Force 36

5.4 Electrical 37

5.4.1 Contact Resistance 37

Appendix A Abbreviations and Acronyms 38

Appendix B Requirements for Aerospace Applications 39

Figures

Figure 1-1 Schematic of Longitudinal (a) and Transverse (b) Cross-Section of a Compliant Press-Fit Connection. 4

Figure 1-2 Examples of Interface Contacts, Compliant Press-Fit Pin and Plated-Through Hole. 5

Figure 4-1 Elasticity Test Tool with Compliant Press-Fit Pin on the Left and Closed Tool on the Right (drawing is not to scale). 13

Figure 4-2 Typical Spring Force Diagrams and A Corrective Curve. 13

Figure 4-3 Regions of Interest for Visual Inspection of a Press-Fit Joint 14

Figure 4-4 Test Setup for the 4-Point Resistance Measurement 14

Figure 4-5 Test Setup for the Push-Out Test 15

Figure 4-6 Schematic Force Versus Distance/ Displacement Graph Obtained in A Push-Out Test 15

Figure 4-7 Indication of Plane for Transverse Cross-Section 15

Figure 4-8 Indication of Planes for Longitudinal Cross-Sections 16

Figure 4-9 Lateral PTH Deformation a and Remaining Metallization b Cross-Sections 16

Figure 4-10 Remaining Metallization b, Deformation of Inner Layers (Jet Effect) j and Whitening of Printed Board w 16

Figure 4-11 Cracks in Circles 17

Figure 5-1 19

Figure 5-2 19

Figure 5-3 19

Figure 5-4 20

Figure 5-5 20

Figure 5-6 21

Figure 5-7 21

Figure 5-8 21

Figure 5-9 22

Figure 5-10 22

Figure 5-11 Cracking of Solder Resist 22

Figure 5-12 23

Figure 5-13 23

Figure 5-14 Indications of Delamination (Whitening) 23

Figure 5-15 24

Figure 5-16 24

Figure 5-17 24

Figure 5-18 25

Figure 5-19 25

Figure 5-20 25

Figure 5-21 26

Figure 5-22 27

Figure 5-23 27

Figure 5-24 27

Figure 5-25 28

Figure 5-26 28

Figure 5-27 $j = 125 \mu\text{m}$ 28

Figure 5-28 29

Figure 5-29 29

Figure 5-30 29

Figure 5-31 30

Figure 5-32 31

Figure 5-33 31

Figure 5-34 31

Figure 5-35 32

Figure 5-36 32

Figure 5-37 33

Figure 5-38 33

Figure 5-39 34

Figure 5-40 34

Figure 5-41 35

Figure 5-42 35

Figure 5-43 35

Tables

Table 3-1 Examples of Common Press-Fit Applications 7

Table 4-1 Test Sequence 10

Table 4-2 Qualification Tests Required for Initial Qualification and Changes in Production 12

Table 4-3 Test Conditions for Temperature Cycle 17

Table 5-1 Whisker Documentation 26

Table 5-2 Typical Minimum Push-Out Forces for Compliant Press-Fit Zone of Different Material Thickness Pertaining to Nominal Hole Sizes 36

Press-Fit Standard for Automotive Requirements and Other High-Reliability Applications

1 Scope This standard prescribes practices for the characterization, qualification and acceptance requirements of compliant press-fit technology for printed boards that cover the manufacturability and reliability needs for high reliability applications intended for use in harsh environments such as automotive and aerospace.

Additional requirements for aerospace applications in Appendix B may apply.

1.1 Purpose This standard prescribes practices for the characterization, qualification and acceptance requirements of compliant press-fit technology for printed boards.

Standards may be updated at any time, including with the use of amendments. The use of an amendment or newer revision is not automatically required. The revision in effect **shall** be as specified by the user.

1.2 Classification

CLASS 1 General Electronic Products

Includes products suitable for applications where the major requirement is function of the completed assembly.

CLASS 2 Dedicated Service Electronic Products

Includes products where continued performance and extended life is required, and for which uninterrupted service is desired but not critical. Typically, the end-use environment would not cause failures.

CLASS 3 High Performance/Harsh Environment Electronic Products

Includes products where continued high performance or performance-on-demand is critical, equipment downtime cannot be tolerated, end-use environment may be uncommonly harsh, and the equipment must function when required, such as life support or other critical systems.

All requirements in this standard pertain to IPC Class 3. When this standard is contractually required, IPC Class 3 requirements **shall** be adopted for all other contractually required standards.

1.3 Measurement Units This standard uses International System of Units (SI units) per ASTM SI10, IEEE/ASTM SI 10, Section 3 [Imperial English equivalent units are in brackets for convenience]. The SI units used in this standard are millimeters (mm) [in] for dimensions and dimensional tolerances, Celsius (°C) [°F] for temperature and temperature tolerances, grams (g) [oz] for weight, and lumens (lm) [footcandles] for illuminance.

Note: This standard uses other SI prefixes (ASTM SI10, Section 3.2) to eliminate leading zeroes (for example, 0.0012 mm becomes 1.2 µm) or as an alternative to powers-of-ten (3.6 x 10³ mm becomes 3.6 m).

1.3.1 Verification of Dimensions When an inspection is done on an assembly, measuring dimensions and determining percentages listed in the standard are not required unless there is a doubt or a question is raised about the acceptance of the product. When there is a doubt or a question is raised, then a referee determination should be implemented, at which time measurements should be made or percentages calculated using the referee magnifications defined in the Standard. For determining conformance to the specifications in this standard, round all observed or calculated values “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding method of ASTM Practice E29. For example, specifications of 2.5 mm max, 2.50 mm max, or 2.500 mm max, round the measured value to the nearest 0.1 mm, 0.01 mm, or 0.001 mm, respectively, and then compare to the specification number cited.

1.4 Definition of Requirements The words “**shall**” or “**shall not**” are used in the text of this document wherever there is a requirement for materials, preparation, process control or acceptance.

The word “should” reflects recommendations and is used to reflect general industry practices and procedures for guidance only.

Line drawings and illustrations are depicted herein to assist in the interpretation of the written requirements of this standard. The text takes precedence over the figures.